



## Safety Data Sheet

bluechem  
GROUP

According to the Model WHS Regulations and the ADG code

### Guard Fill Diesel

Revision date: 13.06.2017

Product code: 1966

Page 1 of 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Guard Fill Diesel

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Cleaning agent for Diesel Systems

### 1.3. Details of the supplier of the safety data sheet

Company name: Bluechem Australia  
Street: Unit 2, 102-110 NORTH VIEW DRIVE  
Place: 3020 SUNSHINE, VICTORIA, AUSTRALIA  
Telephone: (03) 9311 4456      Telefax: (03) 9311 7712  
e-mail: admin@bluechemaustralia.com.au  
Contact person: Neil Cochrane  
Internet: www.bluechemaustralia.com.au

### 1.4. Emergency telephone number:

Emergency 24 HOUR: Neil Cochrane (03) 9311 4456 or 0498 880 115

### Further Information

Article Number: 33033

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS CHEMICAL ACCORDING TO SAFE WORK AUSTRALIA AND WHS CRITERIA.  
CLASSIFIED AS DANGEROUS GOODS ACCORDING TO THE ADG CODE.  
POISON SCHEDULE: 5

#### Classification according to WHS

Hazard categories:  
Flammable liquid: Flam. Liq. 4  
Aspiration hazard: Asp. Tox. 1  
Carcinogenicity: Carc. 2  
Specific target organ toxicity - repeated exposure: STOT RE 1  
Hazardous to the aquatic environment: Aquatic Chronic 2  
Hazard Statements:  
Combustible liquid.  
May be fatal if swallowed and enters airways.  
Suspected of causing cancer.  
Causes damage to organs through prolonged or repeated exposure.  
Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Labeling according to WHS

#### Component(s) to be indicated on the label

Distillates (petroleum, gasoline), hydrotreated light 50 -< 70 %  
2-Ethyl hexyl nitrate 20 -< 25 %  
Hydrocarbons, C10, aromatics, >1% naphthalene 1 -< 5 %  
Solvent naphtha (petroleum, gasoline), heavy aromatic < 1 %

Signal word:            Danger

## Guard Fill Diesel

Revision date: 13.06.2017

Product code: 1966

Page 2 of 9

### Pictograms:



health hazard - environment

### Hazard statements

- H227 Combustible liquid.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H304 May be fatal if swallowed and enters airways.
- H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe vapour/aerosole.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P273 Avoid release to the environment.
- P280 Wear protective gloves and eye/face protection.
- P281 Use personal protective equipment as required.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P331 Do NOT induce vomiting.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of this material and its container to hazardous or special waste collection point.

### Special labelling of certain mixtures

- AUH044 Risk of explosion if heated under confinement.
- AUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Surface tension compounds  
Detergents, Dispersants  
Synthetic agent combinations  
corrosion preventing agent  
Multifunction Diesel Fuel Additive



# Safety Data Sheet

bluechem  
GROUP

According to the Model WHS Regulations and the ADG code

## Guard Fill Diesel

Revision date: 13.06.2017

Product code: 1966

Page 3 of 9

### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to WHS criteria			
64742-82-1	Distillates (petroleum, gasoline), hydrotreated light			50 - < 70 %
	919-164-8		01-2119473977-17	
	Flam. Liq. 4, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H227 H372 H304 H412 AUH066			
27247-96-7	2-Ethyl hexyl nitrate			20 - < 25 %
	248-363-6		01-2119539586-27	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Aquatic Chronic 2; H302 H312 H332 H411 AUH044 AUH066			
64742-94-5	Hydrocarbons, C10, aromatics, >1% naphthalene			1 - < 5 %
	919-284-0		01-2119463588-24	
	Carc. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H351 H336 H304 H411			

Full text of H and AUH phrases: see section 16

### Further Information

According to note P to labelling (Australian Hazardous Substances Information System (HSIS)), "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

#### After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .  
Subsequently wash off with: Water and soap.

#### After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult physician.

#### After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.  
Irritation of eyes: Irritant effect possible.  
After ingestion: Harmful: may cause lung damage if swallowed.

### 4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Extinguishing powder.  
Sand.  
Carbon dioxide (CO2).  
alcohol resistant foam.



## Safety Data Sheet

bluechem   
GROUP

According to the Model WHS Regulations and the ADG code

### Guard Fill Diesel

Revision date: 13.06.2017

Product code: 1966

Page 4 of 9

#### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.  
In case of fire and/or explosion do not breathe fumes.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.  
HAZCHEM: .3Z

#### Additional information

Cool endangered container in case of fire.  
Beat down gas/vapours/mist with water spray.  
Contaminated fire-fighting water must be collected separately.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear a self-contained breathing apparatus and chemical resistant suit.  
Keep away from sources of ignition. - No smoking.

#### 6.2. Environmental precautions

Beat down gas/vapours/mist with water spray.  
Do not allow to enter into surface water or drains.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).  
Prevent spread over a wide area (e.g. by containment or oil barriers).

#### 6.4. Reference to other sections

Information for safe handling look up chapter 7.  
Information for personal protective equipment look up chapter 8.  
Information for disposal see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

The substance should only be handled in closed apparatus or systems. Vapours / aerosols must be extracted by suction immediately at point of origin.  
Avoid contact with skin and eyes.

##### Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.  
Take precautionary measures against static discharges.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

#### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational Exposure Limits (OEL) - Australia

No data available

**Guard Fill Diesel**

Revision date: 13.06.2017

Product code: 1966

Page 5 of 9

**8.2. Exposure controls****Protective and hygiene measures**

- Take off immediately all contaminated clothing
- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin and eyes.
- Keep away from food, drink and animal feeding stuffs.
- When using do not eat, drink or smoke.
- Wash hands before breaks and after work.

**Eye/face protection**

- Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

**Hand protection**

- Tested protective gloves are to be worn: NBR (Nitrile rubber). FKM (Fluoroelastomer (Viton)). (EN374)

**Skin protection**

- Wear suitable solvent-proof protective clothing according to EN 465.

**Respiratory protection**

- In case of accumulation of fumes/aerosols, provide adequate ventilation.
- In case of fire: Wear self-contained breathing apparatus.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	yellow, transparent
Odour:	aromatic

**Test method****Changes in the physical state**

Initial boiling point and boiling range:	200 - 210 °C
Flash point:	62 °C
Density (at 20 °C):	0.83 - 0.87 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	insoluble

**Solubility in other solvents**

- Organic solvents

**9.2. Other information**

No data

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No decomposition when used as intended.

**10.3. Possibility of hazardous reactions**

No dangerous reactions are known.

**10.4. Conditions to avoid**

- Only use the material in places where open light, fire and other flammable sources can be kept away.
- No decomposition when used as intended.

**10.5. Incompatible materials**

- Oxidizing agents.

## Guard Fill Diesel

Revision date: 13.06.2017

Product code: 1966

Page 6 of 9

acid, concentrated.  
Alkalis (alkalis), concentrated.

### 10.6. Hazardous decomposition products

No hazardous decomposition products are known.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
64742-82-1	Distillates (petroleum, gasoline), hydrotreated light			
	oral	LD50 >5000 mg/kg	Rat	
	dermal	LD50 >3400 mg/kg	Rabbit	
27247-96-7	2-Ethyl hexyl nitrate			
	oral	LD50 >9640 mg/kg	Rat	
	dermal	LD50 >4820 mg/kg	Rabbit	
	inhalative vapour	ATE 11 mg/l		
	inhalative aerosol	ATE 1,5 mg/l		

#### Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.  
Irritation of eyes: Irritant effect possible.

#### Sensitising effects

no danger of sensitization.

## SECTION 12: Ecological information

### 12.1. Toxicity

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d]	Species	Source
64742-82-1	Distillates (petroleum, gasoline), hydrotreated light				
	Acute fish toxicity	LC50 10-100 mg/l	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50 50-100 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 10-22 mg/l	48 h	Daphnia magna	
27247-96-7	2-Ethyl hexyl nitrate				
	Acute fish toxicity	LC50 2 mg/l	96 h	Fish	
	Acute algae toxicity	ErC50 1-10 mg/l	72 h	Algae	
	Acute crustacea toxicity	EC50 >10 mg/l	48 h	Daphnia magna	
64742-94-5	Hydrocarbons, C10, aromatics, >1% naphthalene				
	Acute fish toxicity	LC50 2-5 mg/l	96 h	Fish	
	Acute algae toxicity	ErC50 1-3 mg/l	72 h	Algae	
	Acute crustacea toxicity	EC50 3-10 mg/l	48 h	Daphnia magna	

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

## Guard Fill Diesel

Revision date: 13.06.2017

Product code: 1966

Page 7 of 9

Swims on the water.  
Low potential of bio-accumulation.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

No information available.

### 12.6. Other adverse effects

No information available.

### Further information

Do not allow to enter into surface water or drains.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Do not dispose with household waste.  
Do not allow to enter into surface water or drains.  
Arrange about the exact waste code with the local waste disposal expert.  
Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

#### Contaminated packaging

Container must be completely emptied.  
Do not pierce, cut up or weld unclean container. (Explosion hazard.)

## SECTION 14: Transport information

### Land transport (ADG)

14.1. UN number: UN 3082  
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
14.3. Transport hazard class(es): 9  
14.4. Packing group: III  
Hazard label: 9



Special Provisions: 274 335 375 601  
Limited quantity: 5 L

#### Other applicable information (land transport)

HAZCHEM: .3Z

### Marine transport (IMDG)

14.1. UN number: UN 3082  
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
14.3. Transport hazard class(es): 9  
14.4. Packing group: III  
Hazard label: 9



Marine pollutant: P

## Guard Fill Diesel

Revision date: 13.06.2017

Product code: 1966

Page 8 of 9

Special Provisions: 274, 335, 969  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-A, S-F

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
Hazard label: 9



Special Provisions: A97 A158 A197  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y964  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 964  
IATA-max. quantity - Passenger: 450 L  
IATA-packing instructions - Cargo: 964  
IATA-max. quantity - Cargo: 450 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: 2-Ethyl hexyl nitrate  
Hydrocarbons, C10, aromatics, >1% naphthalene

### 14.6. Special precautions for user

No information available.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Distillates (petroleum, gasoline), hydrotreated light

#### Additional information

Contains:

> 30 % aliphatic hydrocarbons  
< 5 % aromatic hydrocarbons

#### National regulatory information

Water contaminating class (D): 2 - water contaminating

#### Additional information

POISON SCHEDULE: 5

All components of this mixture are listed on or exempted from AICS.

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.





## Safety Data Sheet

bluechem   
GROUP

According to the Model WHS Regulations and the ADG code

### Guard Fill Diesel

Revision date: 13.06.2017

Product code: 1966

Page 9 of 9

#### SECTION 16: Other information

##### Abbreviations and acronyms

ADG = Australian Code for the Transport of Dangerous Goods by Road & Rail  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk  
HAZCHEM = HAZardous CHEMicals

WHS = Work Health and Safety  
NOHSC = National Occupational Health and Safety Commission (Australia)  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

##### Relevant H and AUH phrases (number and full text)

H227 Combustible liquid.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
AUH044 Risk of explosion if heated under confinement.  
AUH066 Repeated exposure may cause skin dryness or cracking.

##### Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.  
The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*