

Guard Fill - Diesel

Product properties

The Guard Fill Diesel keeps valves, injectors and combustion chambers free of carbonisation, reduces friction inside the engine and protects all metal surfaces from corrosion. The special combination of highly effective additives in the Guard Fill Diesel can reduce fuel consumption by up to 3% and emissions by up to 35% and is gentle to all materials in the engine and the diesel fuel system. Dampness and condensation will be removed and the upper cylinder area is well lubricated and protected. Guard-Fill keeps the engine in good condition during its entire life.

Area of application

For use in diesel powered engines. Recommended for engines with particle filter, turbo and catalytic converter.

Application

Fill directly into the diesel tank.

Consumption

75ml sufficient for 80 liters diesel. Mixing ratio: 1:1000

Reaction time

while engine is running

Technical data

Physical state: liquid

Colour: clear/colourless

Odour: aromatic

Initial boiling point and boiling range: 200 - 210 °C

Flashpoint: 62 °C

Density at 68 °F: 83 - 0.87 g/cm³

Water resistant

Available sizes	Item no.	PU
75ml	33033	24
1000ml	33439	12



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advice. No liability for any printing errors. Technical modifications and errors are exempted.