

Radiator Flush

Product properties

Radiator Flush removes operational deposits in the entire cooling system. It removes also lime and fur deposits, protects against rust and corrosion, dissolves dangerous radiator sludge and cleans water coolers, boilers and heat exchangers. The product makes valves, thermostats and water pumps free again. The use of Radiator Flush increase the reliability and lifetime of the engine. Also the heating and cooling performance will be improved.

Area of application

For use in all cooling water circuits of petrol and diesel engines or industrial equipment

Application

Add the product to the coolant. Start the engine and open the heating valve, run engine for 10-15 min. Drain system completely and flush with fresh water. Refill the system with coolant in line with manufacturer's instructions. We further recommend adding of powemaxx Radiator Conditioner.

Consumption

300 ml sufficient to treat cooling systems of 4 - 8 litres capacity.

Reaction time

15-40 minutes, depending on the size of the system

Technical data

Physical state: liquid

Colour: yellow

Odour: odourless

pH-Value (at 68 °F): 0-1

Melting point: < 0 °C

Initial boiling point and boiling range: > 100 °C

Density at 68 °F: 1,07 g/cm³

Water soluble

Available size	Item no.	PU
300ml	33326	24
1000ml	33322	12
5L	33320	4
25L	33321	1
200L	33325	1



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.